

# CLARK FORKLIFT TRUCKS, LPG/PETROL CGP 30 GM 3.0L



<b>ENGINE GM 3.0L</b> Capacity: 4,7 liter		
<b>USE</b> Normal		<b>CLIMATE</b> Moderate

<b>PRODUCT RECOMMENDATION 1</b> <b>Asyntho 5W-30</b>		
---	--	--

*Check every 10 hours, change every 250 hours*

<b>USE</b> Initial service		<b>CLIMATE</b> Moderate
-------------------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Asyntho 5W-30</b>		
---	--	--

*Change every 50 hours*

<b>TRANSMISSION POWERSHIFT Clark TA-30 1/1</b> Capacity: 14,2 liter		
--	--	--

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agrifluid HT-Plus</b>		
---	--	--

*Check every 3 months/ 500 hours, change every 6 months/ 1000 hours*

<b>USE</b> Initial service		<b>CLIMATE</b> Moderate
-------------------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Agrifluid HT-Plus</b>		
---	--	--

*Change every 50 hours*

<b>HYDRAULIC SYSTEM</b> Capacity: 44 liter (Hydraulic tank)		
--	--	--

<b>USE</b> Normal		<b>CLIMATE</b> Moderate
----------------------	--	----------------------------

<b>PRODUCT RECOMMENDATION 1</b> <b>Perlus H 32</b>		
---	--	--

*Check every 10 hours, change every 2000 hours/ 12 months*

# CLARK FORKLIFT TRUCKS, LPG/PETROL CGP 30 GM 3.0L



## GREASE POINTS/NIPPLES GENERAL

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Change every 250 hours/ 1 months*

## GREASE POINTS/NIPPLES WHEEL BEARINGS

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Change every 2000 hours/ 12 months*

## COOLING SYSTEM

Capacity: 7,5 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Coolant SP 15+</b>	PRODUCT RECOMMENDATION 2 <b>Coolant SP 12</b>	PRODUCT RECOMMENDATION 3 <b>Coolant -38 Organic NF</b>

*Check every 10 hours, change every 2000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*