

# SYM MAXSYM MAXSYM 600I LX60A(2014-2021)



**发动机**  
 润滑油容量: 2,3 升 (干式填充), 润滑油容量: 2 升 (维修填充), 过滤器端盖: 0,1 升

使用 气候  
 正常 地中海

产品推荐 1 Expulsa RR 15W-50		
-----------------------------	--	--

使用 气候  
 正常 温带

产品推荐 1 Expulsa RR 10W-40	产品推荐 2 Expulsa 10W-40	
-----------------------------	--------------------------	--

使用 气候  
 初始操作 地中海

产品推荐 1 Expulsa RR 15W-50		
-----------------------------	--	--

使用 气候  
 初始操作 温带

产品推荐 1 Expulsa RR 10W-40	产品推荐 2 Expulsa 10W-40	
-----------------------------	--------------------------	--

**主齿轮**  
 润滑油容量: 350 cm<sup>3</sup> (干式填充), 润滑油容量: 330 cm<sup>3</sup> (维修填充)

使用 气候  
 正常 温带

产品推荐 1 Gearlube GL-5 85W-140		
---------------------------------	--	--

使用 气候  
 初始操作 温带

产品推荐 1 Gearlube GL-5 85W-140		
---------------------------------	--	--

# SYM MAXSYM MAXSYM 600I LX60A(2014-2021)



## 液压制动系统□

使用	气候
正常	温带
产品推荐 1	
Drauliquid DOT 3	

## 冷却系统□

润滑油容量: 0,35 升 (储存罐), 润滑油容量: 1,5 升 (散热器 + 发动机)□

使用	气候
正常	温带
产品推荐 1	产品推荐 2
Coolant -38 Organic NF	Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.